

■ Cooling Only

Model Name			AMNC09GTUA0	AMNC12GTUA0
Power Supply		V, Ø, Hz	220-240, 1, 50/60	220-240, 1, 50/60
Power Input		W	-	-
Running Current(Max.)		A	0.2	0.2
Casing Color		-	-	-
Dimensions	Body	W × H × D	mm	860 × 132 × 450
		W × H × D	inch	33-27/32 × 5-3/16 × 17-23/32
Weight	Body		kg (lbs)	11.7 (25.8)
	Shipping		kg (lbs)	14.4 (31.7)
Heat Exchanger	(Row × Column × Fins per inch) × No.		-	(2 × 12 × 18) × 1
	Face Area		m ² (ft ²)	0.18 (1.90)
Fan	Type		-	Cross Flow Fan
	Air Flow Rate	H / M / L	m ³ /min	7.5 / 7.3 / 6.8
		H / M / L	ft ³ /min	265 / 258 / 240
Fan Motor	Type		-	BLDC
	Output		W × No.	20 × 1
Sound Pressure Level		H / M / L	dB(A)	36 / 34 / 32
Sound Power Level		H / M / L	dB(A)	-
Piping Connections	Liquid		mm(inch)	Ø 6.35 (1/4)
	Gas		mm(inch)	Ø 9.52 (3/8)
	Drain (O.D. / I.D.)		mm	Ø 32.0 / 25.0
Safety Devices			-	Fuse
Power and Communication Cable (included Earth)			No. × mm ² (AWG)	4C × 0.75 (18)
Decoration Panel 1	Model Name		-	PT-UUC1
	Casing Color		-	Morning Fog
	Dimensions	W × H × D	mm	1,100 × 34 × 500
		W × H × D	inch	43-5/16 × 1-11/32 × 19-11/16
	Net weight		kg (lbs)	4.4 (9.7)
Decoration Panel 2	Model Name		-	PT-UAHG0
	Casing Color		-	White
	Dimensions	W × H × D	mm	1,160 × 34 × 500
		W × H × D	inch	45-21/32 × 1-11/32 × 19-11/16
	Net weight		kg (lbs)	3.9 (8.6)
Decoration Panel 3	Model Name		-	PT-UPHG0
	Casing Color		-	White
	Dimensions	W × H × D	mm	1,160 × 34 × 500
		W × H × D	inch	45-21/32 × 1-11/32 × 19-11/16
	Net weight		kg (lbs)	4.1 (9.0)

■ Heat Pump

Model Name			AMNW09GTUA0	AMNW12GTUA0
Power Supply		V, Ø, Hz	220-240, 1, 50	220-240, 1, 50
			220, 1, 60	220, 1, 60
Power Input		W	-	-
Running Current(Max.)		A	0.2	0.2
Casing Color		-	-	-
Dimensions	Body	W × H × D	mm	860 × 132 × 450
		W × H × D	inch	33-27/32 × 5-3/16 × 17-23/32
Weight	Body		kg (lbs)	11.7 (25.8)
	Shipping		kg (lbs)	14.4 (31.7)
Heat Exchanger	(Row × Column × Fins per inch) × No.		-	(2 × 12 × 18) × 1
	Face Area		m ² (ft ²)	0.18 (1.90)
Fan	Type		-	Cross Flow Fan
	Air Flow Rate	H / M / L	m ³ /min	7.5 / 7.3 / 6.8
		H / M / L	ft ³ /min	265 / 258 / 240
Fan Motor	Type		-	BLDC

Fan motor		Output	W × No.	20 × 1	20 × 1
Sound Pressure Level		H / M / L	dB(A)	36 / 34 / 32	37 / 36 / 33
Sound Power Level		Max.	dB(A)	54	57
Piping Connections	Liquid		mm(inch)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas		mm(inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)
	Drain (O.D. / I.D.)		mm	Ø 32.0 / 25.0	Ø 32.0 / 25.0
Safety Devices			-	Fuse	
			-	Thermal Protector for Fan Motor	
Power and Communication Cable (included Earth)			No. × mm ²	4C x 0.75	4C x 0.75
Decoration Panel 1	Model Name		-	PT-UUC1	PT-UUC1
	Casing Color		-	Morning Fog	Morning Fog
	Dimensions	W × H × D	mm	1,100 × 34 × 500	1,100 × 34 × 500
		W × H × D	inch	43-5/16 × 1-11/32 × 19-11/16	43-5/16 × 1-11/32 × 19-11/16
	Net weight		kg (lbs)	4.4 (9.7)	4.4 (9.7)
Decoration Panel 2	Model Name		-	PT-UAHG0	PT-UAHG0
	Casing Color		-	White	White
	Dimensions	W × H × D	mm	1,160 × 34 × 500	1,160 × 34 × 500
		W × H × D	inch	45-21/32 × 1-11/32 × 19-11/16	45-21/32 × 1-11/32 × 19-11/16
	Net weight		kg (lbs)	3.9 (8.6)	3.9 (8.6)
Decoration Panel 3	Model Name		-	PT-UPHG0	PT-UPHG0
	Casing Color		-	White	White
	Dimensions	W × H × D	mm	1,160 × 34 × 500	1,160 × 34 × 500
		W × H × D	inch	45-21/32 × 1-11/32 × 19-11/16	45-21/32 × 1-11/32 × 19-11/16
	Net weight		kg (lbs)	4.1 (9.0)	4.1 (9.0)

AMNC18GTTA0	AMNC24GTTA0	AMNQ09GTUA0	AMNQ12GTUA0	AMNQ18GTTA0
220-240, 1, 50/60	220-240, 1, 50/60	220-240, 1, 50	220-240, 1, 50	220-240, 1, 50
-	-	-	-	-
0.31	0.31	0.2	0.2	0.31
-	-	-	-	-
1,180 × 132 × 450	1,180 × 132 × 450	860 × 132 × 450	860 × 132 × 450	1,180 × 132 × 450
46-15/32 × 5-3/16 × 17-23/32	46-15/32 × 5-3/16 × 17-23/32	33-27/32 × 5-3/16 × 17-23/32	33-27/32 × 5-3/16 × 17-23/32	46-15/32 × 5-3/16 × 17-23/32
14.5 (32.0)	14.5 (32.0)	11.7 (25.8)	11.7 (25.8)	14.5 (32.0)
17.9 (39.5)	17.9 (39.5)	14.4 (31.7)	14.4 (31.7)	17.9 (39.5)
(2 × 12 × 18) × 1	(2 × 12 × 18) × 1	(2 × 12 × 18) × 1	(2 × 12 × 18) × 1	(2 × 12 × 18) × 1
0.24 (2.58)	0.24 (2.58)	0.18 (1.90)	0.18 (1.90)	0.24 (2.58)
Cross Flow Fan	Cross Flow Fan	Cross Flow Fan	Cross Flow Fan	Cross Flow Fan
13.3 / 11.8 / 10.8	14.0 / 13.3 / 11.8	7.5 / 7.3 / 6.8	8.1 / 7.4 / 7.0	13.3 / 11.8 / 10.8
470 / 417 / 381	494 / 470 / 417	265 / 258 / 240	286 / 261 / 247	470 / 417 / 381
BLDC	BLDC	BLDC	BLDC	BLDC
30 × 1	30 × 1	20 × 1	20 × 1	30 × 1
41 / 39 / 36	44 / 41 / 39	36 / 34 / 32	37 / 36 / 33	41 / 39 / 36
-	-	-	-	-
Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
Ø 12.7 (1/2)	Ø 12.7 (1/2)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)
Ø 32.0 / 25.0	Ø 32.0 / 25.0	Ø 32.0 / 25.0	Ø 32.0 / 25.0	Ø 32.0 / 25.0
Fuse		Fuse		Fu
Thermal Protector for Fan Motor		Thermal Protector for Fan Motor		Thermal Protect
4C × 0.75 (18)	4C × 0.75 (18)	4C × 0.75 (18)	4C × 0.75 (18)	4C × 0.75 (18)
PT-UTC	PT-UTC	PT-UUC1	PT-UUC1	PT-UTC
Morning Fog	Morning Fog	Morning Fog	Morning Fog	Morning Fog
1,420 × 34 × 500	1,420 × 34 × 500	1,100 × 34 × 500	1,100 × 34 × 500	1,420 × 34 × 500
55-29/32 × 1-11/32 × 19-11/16	55-29/32 × 1-11/32 × 19-11/16	43-5/16 × 1-11/32 × 19-11/16	43-5/16 × 1-11/32 × 19-11/16	55-29/32 × 1-11/32 × 19-11/16
5.0 (11.0)	5.0 (11.0)	4.4 (9.7)	4.4 (9.7)	5.0 (11.0)
PT-TAHG0	PT-TAHG0	PT-UAHG0	PT-UAHG0	PT-TAHG0
White	White	White	White	White
1,480 × 34 × 500	1,480 × 34 × 500	1,160 × 34 × 500	1,160 × 34 × 500	1,480 × 34 × 500
58-9/32 × 1-11/32 × 19-11/16	58-9/32 × 1-11/32 × 19-11/16	45-21/32 × 1-11/32 × 19-11/16	45-21/32 × 1-11/32 × 19-11/16	58-9/32 × 1-11/32 × 19-11/16
4.8 (10.6)	4.8 (10.6)	3.9 (8.6)	3.9 (8.6)	4.8 (10.6)
PT-TPHG0	PT-TPHG0	PT-UPHG0	PT-UPHG0	PT-TPHG0
White	White	White	White	White
1,480 × 34 × 500	1,480 × 34 × 500	1,160 × 34 × 500	1,160 × 34 × 500	1,480 × 34 × 500
58-9/32 × 1-11/32 × 19-11/16	58-9/32 × 1-11/32 × 19-11/16	45-21/32 × 1-11/32 × 19-11/16	45-21/32 × 1-11/32 × 19-11/16	58-9/32 × 1-11/32 × 19-11/16
4.9 (10.8)	4.9 (10.8)	4.1 (9.0)	4.1 (9.0)	4.9 (10.8)

AMNW18GTTA0
220-240, 1, 50
220, 1, 60
-
0.31
-
1,180 × 132 × 450
14.5 (32.0)
17.9 (39.5)
(2 × 12 × 18) × 1
0.24 (2.58)
Cross Flow Fan
13.3 / 11.8 / 10.8
470 / 417 / 381
BLDC

30 × 1
45 / 42 / 39
59
Ø 6.35 (1/4)*
Ø 12.7 (1/2)*
Ø 32.0 / 25.0
Fuse
Thermal Protector for Fan Motor
4C x 0.75
PT-UTC
Morning Fog
1,420 × 34 × 500
55-29/32 × 1-11/32 × 19- 11/16
5.0 (11.0)
PT-TAHG0
White
1,480 × 34 × 500
58-9/32 × 1-11/32 × 19- 11/16
4.8 (10.6)
PT-TPHG0
White
1,480 × 34 × 500
58-9/32 × 1-11/32 × 19- 11/16
4.9 (10.8)

AMNQ24GTTA0
220-240, 1, 50
-
0.31
-
1,180 × 132 × 450
46-15/32 × 5-3/16 × 17-23/32
14.5 (32.0)
17.9 (39.5)
(2 × 12 × 18) × 1
0.24(2.58)
Cross Flow Fan
14.0 / 13.3 / 11.8
494 / 470 / 417
BLDC
30 × 1
44 / 41 / 39
-
Ø 6.35 (1/4)
Ø 12.7 (1/2)
Ø 32.0 / 25.0
se
or for Fan Motor
4C x 0.75 (18)
PT-UTC
Morning Fog
1,420 × 34 × 500
55-29/32 × 1-11/32 × 19-11/16
5.0 (11.0)
PT-TAHG0
White
1,480 × 34 × 500
58-9/32 x 1-11/32 x 19-11/16
4.8 (10.6)
PT-TPHG0
White
1,480 × 34 × 500
58-9/32 x 1-11/32 x 19-11/16
4.9 (10.8)